

BUILDING TERMS

Article Test (17)

Match the number with the corresponding letter

- | | | | |
|-----|----------------|----|---|
| 1. | vapour barrier | A. | A mineral closely relate to mica, used in insulation |
| 2. | truss | B. | Horizontal board in a stairway on which the foot is placed |
| 3. | panel box | C. | 2 or 3-prong connector used to establish a circuit by fitting into a receptacle |
| 4. | riser | D. | A thin mortar used for filling spaces |
| 5. | keystone | E. | A small column used to support a rail |
| 6. | stanchion | F. | Piece of aluminum used around dormers, chimney, et cetera |
| 7. | vermiculite | G. | A large timber or steel member |
| 8. | male plug | H. | A low wall or railing to protect the edge of a platform or roof |
| 9. | fascia | I. | An assemblage of members (as beams) forming a rigid framework |
| 10. | jamb | J. | A box in which electric switches for branch circuits are located |
| 11. | baluster | K. | Joint made by cutting two pieces at an angle and fitting together |
| 12. | flashing | L. | Vertical boards closing the spaces within the treads of stairways |
| 13. | tread | M. | A steel beam with a cross section resembling the letter "I" |
| 14. | grout | N. | A column or post |
| 15. | parapet | O. | Material used to retard the flow of vapour or moisture into walls |
| 16. | I-beam | P. | Piece of wood made of here or more layers of veneer joined with glue |
| 17. | miter | Q. | The trimming around a door or window opening |
| 18. | plywood | R. | The side post or lining of a doorway, window, or other opening |
| 19. | girder | S. | The stone placed in the center of the top of an arch |
| 20. | casing | T. | Flat board, band, or face generally used with moldings |